

Featuring
Bluetooth®



4FRONT®
shown in *Electric Blue*
with Safe Seat Elevation

QUANTUM® **4FRONT®**

The 4Front® is a quiet, more responsive front-wheel drive power chair with unprecedented comfort and ride quality. The 4Front's CASE (Caster Angle Sensor Encoder) technology and SRS (Smooth Ride Suspension) provide stability for smooth obstacle transitions and unmatched driving performance. The 4Front features standard speeds of up to 6 mph in the lowered position, and speeds up to 3.2 mph while elevated at 10" with our optional safe seat elevation.

QUANTUM®

Specifications

DRIVE WHEELS	Standard: 14" flat free Optional: 14" knobby
CASTER WHEELS	Rear: 9" flat free
ANTI-TIP WHEELS	Front: 4"
MAXIMUM SPEED ¹	Up to 6 mph
GROUND CLEARANCE	3" (motor pivot)
TURNING RADIUS ²	24.5"
OVERALL LENGTH ²	40"
BASE WIDTH	24"
SEATING SIZES	
TRU-Balance® 3 Static Seat	Width: 12-22" Depth: 12-22"
TRU-Balance® 3 Power Tilt	Width: 12-22" Depth: 12-22"
TRU-Balance® 3 Lift & Tilt	Width: 12-22" Depth: 12-22"
SEAT-TO-FLOOR HEIGHTS ⁹	
TRU-Balance® 3 Static Seat ⁵	15.25-17.25"
TRU-Balance® 3 Power Tilt ⁵	17.5-19.5"
TRU-Balance® 3 Lift & Tilt ⁵	17.75-19.75"
MANUAL RECLINE	Yes
BATTERY SIZE ³	Group 24 or Group 34
BATTERY WEIGHT ⁶	Group 24: 51.5 lbs. Group 34: 38.5 lbs.
AVAILABLE ELECTRONICS ⁷	120A Q-Logic 3 EX
BATTERY CHARGER	8A Off-board
MOTOR PACKAGES	Two-pole, front-wheel drive
WEIGHT CAPACITY ⁴	300 lbs.
BASE WEIGHT	140 lbs.
MEDICARE CODE COVERAGE	Group 3: Standard (K0848/K0849), Single Power (K0856), Multiple Power (K0861)

1) Speed varies with user weight, terrain type, battery charge, battery condition and tire pressure.

2) Without front riggings

3) Battery capacity may change when adding power positioning systems.

4) Weight capacity is dictated by the selection of seating.

5) All measurements +/- 1/8" with 18" x 18" seat, fixed towers, 300 lbs. weight capacity and solid tires (add 3/8" with pneumatic tires). Widths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.

6) Battery weight may vary +/- 3 lbs. based on manufacturer.

7) All Quantum Rehab® units can be ordered with specialty controls.

8) Call for availability

9) Seat-to-floor heights are measured with the unit unloaded. Due to the 4Front's suspension system, seat-to-floor heights are approximately 0.25" lower when the unit is loaded.

Standard Features

- CASE (Caster Angle Sensor Encoder) technology
- Unmatched driving performance and ride quality
- Advanced stability for smooth obstacle transitions
- Superior, automotive-grade SRS (Smooth Ride Suspension)
- Q-Logic 3 EX Advanced Drive Controls
- LED front and rear fender lights
- Quiet ride technology

Options

- 10" of power adjustable safe seat elevation at speeds of up to 3.2 mph
- TRU-Balance® 3 Seating
- TRU-Comfort 2 Seating
- Trilogy vent tray ⁸
- Compact vent tray ⁸
- WC19 crash-test approved occupied transit option on all configurations

Colors



Hydrographics

